

CONSTRUCTION TABLE :


Number of cores	Size of conductor		Thickness (mm ± 0.1)	Width (mm)	Allowable error (mm)
	(AWG)	Composition (strands/mm)			
9	28	7/0.127	0.9	11.43	±0.30
10	28	7/0.127	0.9	12.70	±0.30
14	28	7/0.127	0.9	17.78	±0.30
15	28	7/0.127	0.9	19.05	±0.30
16	28	7/0.127	0.9	20.32	±0.30
20	28	7/0.127	0.9	25.40	±0.30
25	28	7/0.127	0.9	31.75	±0.30
26	28	7/0.127	0.9	33.02	±0.30
30	28	7/0.127	0.9	38.10	±0.30
34	28	7/0.127	0.9	43.18	±0.40
36	28	7/0.127	0.9	45.72	±0.40
40	28	7/0.127	0.9	50.80	±0.40
50	28	7/0.127	0.9	63.50	±0.40
60	28	7/0.127	0.9	76.20	±0.40
64	28	7/0.127	0.9	81.28	±0.40

FLAT CABLE WRC



HFR-28R3HF-xx-LF
 T
 LEADFREE

RoHS Compliant

 焯倫股份有限公司	PART NO. HFR-28R3HF-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:			
	UNIT / mm	SCALE 1:1			DRAWING BY	AREA	REVISIONS	HK

