



QMFZ2 Component - Plastics

Friday, October 24, 2003

E55519

**DOW CORNING TORAY SILICONE CO LTD**

CHIBA PLANT 2-2 CHIGUSA-KAIGAN ICHIHARA-SHI CHIBA-KEN 299-0108 JP

Material Designation: **B6650INT**

Product Description: Silicone (SI), w/ vulcanizing agent RC-4 (50P) FD, furnished as uncured w/ vulcanizing agent.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.83	HB	-	-	150	150	150	-	-
CTI: - IEC CTI: -		HVTR: -			D495: -		IEC Ball Pressure (°C): -		
Dielectric Strength (kV/mm): -		Volume Resistivity (10 <sup>x</sup> ohm-cm): -					Dimensional Stability(%): -		
ISO Tensile Strength (MPa): -		ISO Flexural Strength (MPa): -					ISO Heat Deflection (°C): -		
ISO Tensile Impact (kJ/m <sup>2</sup> ): -		ISO Izod Impact (kJ/m <sup>2</sup> ): -					ISO Charpy Impact (kJ/m <sup>2</sup> ): -		

Report Date: 3/7/1991

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.